

ENVIRONMENT SENSOR PROBE (Humidity & Temperature Solutions)






Current / Voltage Output Sensor



I Vibes II RhT Sensors on IoT Platform



Rh T Con **Indicator Controller**



AGROCHEMICAL | EXHIBITS AND ARCHIVES | ELECTRONICS | CHEMICAL | AUTOMOTIVE & AEROSPACE INTERNET OF THINGS (IOT) | CERAMIC & BRICKS



SeethaRam Mechatronics Pvt Ltd







www.seetharam.in



Variants Output Version

- Current: 4~20mA
- Voltage: 0~3.3V DC
- IoT (HTTP, MOOT)
- · Display Logger
- Indicator Controller

Housing

- ABS Plastic
- Metal Aluminium Grade 6xxx series



Humidity measurement range 0 to 100 % RH



Temperature range of 40°C to 125°C

Working Temperature

- Normal Temperature: upto 85° C
- High Temperature: upto 125° C



Typical accuracy ranges of ±2% RH



Typical accuracy ranges of ±0.2% °C

Industrial Measurements

- Food, Beverage & Agriculture
- HVAC & Indoor Air
- Compressed Air
- · Power Transformer
- Semiconductor
- Automotive
- Data Centers
- Fuel Cells

- Pulp, Paper and Wood
- Warehouses
- · Battery Manufacturing
- · Chemicals & Allied Products
- Life Science & Pharmaceutical
- Sugar
- Sweeteners
- Biogas
- Cleanrooms

- Oil & Gas Refilling & Petrochemicals
- Research Facilities & Metrology
- Scientific & Laboratory Equipment
- · Weather Station
- · Engineering Projects
- Green house / Hoop house
- Horticulture



HVAC



Scientific & Laboratory Equipment



Green house / Hoop house



Weather Station

