Home Screen

F

Spring testing systems are ideal for high volume production testing, quality control inspection, and design engineering. The force sensor (Load-cell) is fixed inline and displacement sensor in parallel to the actuation cylinder/ ram compressing the spring under test. The force vs displacement data gives the analysis of the subject spring. The spring performance analysis is a must for all critical assemblies in which the spring is an important constituent.



Real time value of 3 load cell and a displacement sensor with peak and zero option

	11-04-2016 05:57:00 PM	Memory Stat		1.2 MB			 2
			Data Lo	gging			
		Enable Logging	Ø				
			Threshold Apply				
Display			T3	A	arm Enable	P	
		am	CH1				
		Alarm Condition :	-				
\sim		Alarm Channel :	20 -				
Data Logging		Alarm value :					
		Asarri value .					
			Save Se	tings			
Live Graph			Data Loggin				

Enable logging and alarm. Set condition for alarm

- XO

Specifications are subject to change without notice

SPRING TEST LOGGER

11-04-201	16 05:57:54 PM Me	emory Stat	tus :	_	.2 MB		
	Nan	ne: C1		Channel	14		
—	Input ty	pe: Lo	ad	14			
Display							
	U	nit: Kg	1	^v	Decimal :	3	
	I and Value	ge: 0			1 Park Malkana	10	
Data Logging	Low Volta	ge: u			High Voltage :	10	
	Low Val	ue: 0	10 m		High Value :	1	
				Save Sett	inas		
Live Graph					n and Settings		

Individual Channel Calibration - Channel Name, Units & Scale Values user configurable











